

Portable pH Meters



- User-selectable “calibration time out”
- Automatic calibration
- Automatic Temperature Compensation
- Tutorial messages on LCD
- BEPS (Battery Error Prevention System) alerts the user in the event that low battery power could adversely affect readings
- Battery % displayed on startup.

The HI 9124 and HI 9125 are waterproof pH meters. The HI 9125 can utilize ORP (oxidation reduction potential) electrodes.

A large dual-level LCD displays both the pH and temperature along with an operational guide. Graphic symbols are displayed to help the users during the calibration process.

The pH calibration procedure is automatic with five memorized pH buffer values and buffer recognition to simplify the calibration process.

These meters utilize the HI 1230B double junction pH electrode. The double junction helps to minimize junction contamination for accurate, consistent results.

| SPECIFICATIONS | | HI 9124 | HI 9125 |
|--------------------------|-------------|--|---------------------|
| Range | pH | -2.00 to 16.00 pH | |
| | mV | - | ±699.9 mV; ±1999 mV |
| | Temperature | -20.0 to 120.0°C/-4.0°F to 248.0°F | |
| Resolution | pH | 0.01 pH | |
| | mV | - | 0.1 mV; 1 mV |
| | Temperature | 0.1°C/0.1°F | |
| Accuracy (@20°C/60°F) | pH | ±0.01 pH | |
| | mV | - | ±0.2 mV; ±1 mV |
| | Temperature | ±0.4°C/±0.8°F (excluding probe error) | |
| pH Calibration | | automatic, one or two point with five standard buffer values (pH 4.01, 6.86, 7.01, 9.18, 10.01) | |
| Offset Calibration | | ±1 pH | |
| Slope Calibration | | from 80 to 108% | |
| Temperature Compensation | | automatic or manual, -20.0 to 120.0°C/-4.0 to 248.0°F without temperature probe | |
| Electrode | | HI 1230B PEI body pH electrode with BNC connector and 1 m (3.3') cable (included) | |
| Temperature Probe | | HI 7662 stainless steel temperature probe with 1 m (3.3') cable (included) | |
| Input Impedance | | 10 ¹² Ohm | |
| Battery Type / Life | | 1.5V AAA (3) / approximately 200 hours of continuous use. auto-off after 20 minutes of non-use (can be disabled) | |
| Environment | | 0 to 50°C (32 to 122°F); RH max 100% | |
| Dimensions | | 185 x 72 x 36 mm (7.3 x 2.8 x 1.4") | |
| Weight | | 300 g (10.6 oz.) | |

ORDERING INFORMATION

HI 9124 and HI 9125 are supplied with HI 1230B pH electrode, HI 7662 temperature probe, HI 70004 pH 4.01 buffer solution sachet, HI 70007 pH 7.01 buffer solution sachet, 100 mL plastic beaker, batteries, instructions and hard carrying case.

ELECTRODES

| | |
|----------|---|
| HI 1230B | PEI body pH electrode with BNC connector and 1 m (3.3') cable |
| HI 3131B | Glass body ORP electrode with platinum sensor, BNC connector and 1 m (3.3') cable |
| HI 7662 | Stainless steel temperature probe with 1 m (3.3') cable |

SOLUTIONS

| | |
|-----------|-------------------------------------|
| HI 5004L | pH 4.01 buffer solution, 500 mL |
| HI 5007L | pH 7.01 buffer solution, 500 mL |
| HI 5010L | pH 10.01 buffer solution, 500 mL |
| HI 70300L | Electrode storage solution, 500 mL |
| HI 7061L | Electrode cleaning solution, 500 mL |