



conductivity plus Conductivity Meter

Tape options: 100ft/30m to 1000ft/300m

Warranty: 3 years, probe 1 year

The **conductivity plus** enables accurate measurements of **conductivity**, **water levels** and **temperatures** in wells, boreholes, stand pipes and estuaries where salt water intrusion and contamination levels become a concern. **Conductivity** can be an early indicator of change in a water system due to fluctuations of salinity in water levels.

The high tensile steel core measuring tape is tested for stretch resistance to **ASME standards** and is ideal for profiling up to **50°C**. An LCD screen displays conductivity values up to **80,000 μS** and temperature range from **0°C - 50°C**. The conductance temperature compensation coefficient is 2.0%. Calibration of the **conductivity plus** is easy using readily available 1413 μS solution.

Features included with the conductivity plus:

- **Electronic Module (IP65)** – LCD screen displays conductivity values up to **80,000 μS** and a temperature range from **0°C - 50°C**, removable for easy cleaning and servicing
- **Auto off facility** - activates after five minutes of 0 conductivity profiling
- **Operating temperature** – **0°C-50°C**
- **Probe (IP68)** – fully pressure/depth rated, 22mm (0.875"), **field replaceable**
- 4 Electrode Configuration system comprising of **2 arrays of single electrode** within a concentric electrode
- **Steel Tape** – high tensile steel, jacketed with **Polyethylene**, high break strength, stretch resistant and lifelong legibility – markings in metric (mm) or engineering scale (1/100')
- **Padded Carry Case** – to protect your **precision** water level meter from the elements
- **Tape Guide and Hanger** – to support the meter at the well head and to **protect** the tape from sharp edges on the well casing
- **Vinyl Holding Grip** – molded to the frame, **ergonomic easy grip**
- **Winding Handle** – custom made for **easy rewinding** with gloved hands



Envirotecnicos Global Service SL
Bureaux et atelier: Calle dels Pirineus s/n (esquina Espinau) 17460
Celrà · Girona · Espagne Tel: +34 872 080 542
Délegation Madrid: Avda. Fuentemar, 20 Nave B-10
Parque Navegando 28823 Coslada · Madrid · Espagne
Tel: + 34 916 780 039
Service client: envirotecnicos@envirotecnicos.com



www.envirotecnicos.com

A-825-1700-001-Rev B_Heron
2021